









TECHNICAL DATA

TRIAC Dimmable all in one PSUs

Specification	Product		
Product code	CL-TD-24-24	CL-TD-40-24	CL-TD-75-24
			
Colour	White	White	Black
Material	Plastic	Plastic	Metal
Wattage	24W	40W	75W
Voltage input	220 – 240V AC	200-240V AC	200 - 240V AC
Voltage output	24V DC Constant voltage	12 or 24V DC Constant voltage	12 or 24V DC Constant voltage
Ampage output	1A @ 24V	1.67A @ 24V	3.1A @ 24V
IP rating	IP20	IP20	IP20
Working temperature	-20°C - +50°C	-20°C - +50°C	-20°C - +50°C
Fixing	Screw mounting	Screw mounting	Screw mounting
Dimmable	Leading edge / trailing edge	Leading edge / trailing edge	Leading edge / trailing edge
Application	Internal Commercial Entertainment Residential	Internal Commercial Entertainment Residential	Internal Commercial Entertainment Residential
Quality			
Grade	Commercial	Commercial	Commercial
CE and RoHS certified	Yes	Yes	Yes
Warranty	2 years	2 years	2 years
Dimensions (mm)			
Length	150	137	188
Width	43	82	52
Height	29	31	35



Specification	Product		
	CL-TD-150-24	CL-TD-200-24	CL-TD-300-24
Product code	CL-TD-150-24	CL-TD-200-24	CL-TD-300-24
			
Colour	Black	Black	Silver
Material	Metal	Metal	Metal
Wattage	150W	200W	300W
Voltage input	200 - 240V AC	220 – 240V AC	200 – 240V AC
Voltage output	12 or 24V DC Constant voltage	12 or 24V DC Constant voltage	12 or 24V DC Constant voltage
Ampage output	6.3A @ 24V	8.3A @ 24V	12.5A @ 24V
IP rating	IP20	IP20	IP65
Working temperature	-20°C - +50°C	-20°C - +50°C	-20°C - +50°C
Fixing	Screw mounting	Screw mounting	Screw mounting
Dimmable	Leading edge / trailing edge	Leading edge / trailing edge	Leading edge / trailing edge
Application	Internal Commercial Entertainment Residential	Internal Commercial Entertainment Residential	Internal Commercial Entertainment Residential
Quality			
Grade	Commercial	Commercial	Commercial
CE and RoHS certified	Yes	Yes	Yes
Warranty	2 years	2 years	2 years
Dimensions (mm)			
Length	310	310	317
Width	60	60	70
Height	45	45	44



Wiring Diagram

